

Scissor and Screw Jack

- * SJ-1.5 is an import.
- This scissor jack is a high quality import distributed by U.S. Jack.
- It is the considered opinion of U.S. Jack that this piece of equipment will meet your expectations in quality and performance.



SJ-1.5

Base Plate 4.25" W x 7.375" L
 Pad or top plate.....1.5" x 5.00
 Low (collapsed) height...4-5/8"
 Raised height13.3125"
 Total lift.....9.1875"
 Number of revolutions required for total lift **32**



Height of top plate in 5 revolution increments of the handle:

No. of rotations	Subsequent Height (inches)
0.....	3.5
5.....	7.0625
10.....	9.0625
15.....	10.5
20.....	11.5625
25.....	12.4375
30.....	13.0625
32.....	13.3125

FEATURES OF THE SJ-1.5 Scissor Jack

- 1-1/2 ton capacity scissor jack with 2– piece removable handle, 22" in overall length when assembled.
- When unit is fully collapsed an envelope area of 4.25" x 10-1/2" will be required for operation.

D-41501 Double Screw Jack Ideal lifting units for boat trailers, campers and medium duty RV's. Also used for adjusting heights on conveyors, lift tables, hoppers, machine tables and many other industrial applications. Two-stage, gear drive lifting mechanism is fully enclosed in a cast aluminum alloy housing. Telescoping steel tubes protect and guide twin-screws.

DIMENSIONAL SPECIFICATION D-41501

Capacity 1.5 Tons
 Base Plate..... 3-7/8" x 3-7/8"
 Pad or Top Plate size.....1.25" x 2"
 Low (collapsed height)6.7"
 Raised height.....16-3/8"
 Total Lift.....9-5/8"
 Number of revolutions required for total lift..... 148
 Total lift per single rotation of the handle..... .0625"



D-41501

