

# Under Hoist Automotive Transmission Jacks 1/2 Ton Capacity (Import )

## 57250 **IMPORT** - TELESCOPIC 1/2 TON CAPACITY SINGLE PUMP

### INTENDED USE

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans, and light trucks that are raised by an in-ground or above-ground lift.

### FEATURES

- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload systems prevents jack from being used beyond its rated capacity.
- Foot operated pump and lowering pedals allow use of both hands to position and align saddle with transmission.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing casters wheels, provide stability and easy maneuvering.
- Polyurethane wheels provide protection for tile and epoxy floors.



Model Number	Capacity (TONS)	Lift Low	Range High	Base Size	Load Fwd	Saddle Back	Tilt Side	Shipping Weight
57250	1/2	35"	72"	34" x 37"	42°	46°	+/- 12°	176 lbs.
57255	1/2	35"	72"	34" x 37"	42°	46°	+/- 12°	178 lbs.

## 57255 **IMPORT** - TELESCOPIC 1/2 TON CAPACITY DOUBLE PUMP

### INTENDED USE

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans, and light trucks that are raised by an in-ground or above-ground lift

### FEATURES

- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload systems prevents jack from being used beyond its rated capacity.
- Foot operated pump and lowering pedals allow use of both hands to position and align saddle with transmission.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing casters wheels, provide stability and easy maneuvering.
- Two times faster rising action as model 57250 with no load or a load up to 400 pounds.
- Same rising action as 57250 for loads between 400 & 1,000 lbs.
- Polyurethane wheels provide protection for tile and epoxy floors.



**OPTIONAL ADAPTERS AND SADDLES ON PAGES 24 AND 25**  
**Models 57204, 57205, 57206, 57207, 57208, 57209, and 57210**